





It adopts a 150CC single-cylinder fourstroke engine, which is naturally aircooled and starts with electric feet



Whole Motorcycle LED Light



Front disc and rear drum brakes are adopted



The vehicle adopts a full LCD instrument

AP150-2E

LINGYUE CG

AP150-2E



Engine

Engine single-cylinder,four-stroke

Engine modl 162FMJ-2

Engine displacement(ml)

Cooling way Natural air cooling

Compress ratio (g/KW.h) 9.2:1

Φ62*49.5 1400+140

Max power (KW/rlmin) 8.5/8500±100 10.5/7000±100 Max. Torque (N.m/rlmin)

Lowest fuel consumption (g/KW.h) < 354

Lubricating system Stress Splash

International Five Gear

Starting way Electric/kick

Max. Speed(KM/H)

Chassis

Front disc rear drumbrakes Dry weight Front 240 / Rear 130 Ways of Brake Hand brake / Foot brake

2.75-18 Front tire Rear tire 3.25-18

Dimensions

1960*820*1130 Wheelbase(mm) 1300mm Rated capacity Rated max. Load(KG)

All contents involved in this detail page are for reference only. Please refer to the actual vehicle

JIANGMEN SULONG VEHICLE MANUFACTURING CO., LTD.

Area A Sulong Industrial Area. Lile Stresst, Jianghai District, Jiangmen City.



f Apuluo Motos

(6) Apuluo Motos



d Apuluo Motos



x sales6@sulong-motor.com

APULUO